

Product Information

Mod.R&S 06 | Rev.4 | Update 08/2019 | Page 1




P.S. PERFOR

Description PU plotter cut heat seal material with adhesive polyester backing featuring bright colors.

> The material grants high washing resistance and an easy cutting, weeding and application. Recommended for multilayer applications. The circular perforation allows transpiration, giving at the same time a unique decorating effect.

> Suitable for cotton, polyester, blends of these materials, not treated or dye sublimated.



Suggested cutting settings

Blade: 45° Pressure: 80 gf Speed: 30 cm/sec

- **Usage** Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - Remove the carrier warm or cold



Transfer settings

15 seconds at 150°C (300°F) medium pressure (3-4 bar)

Washing

Wait at least 24 hours from application before washing. Washing resistance up to **60°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, cotton cycle.

The product is REACH compliant The product is certified Öko-Tex® Standard 100 Class I The product is VEGANOK certified







Washing temperature




Dry cleaning



Tumble dryer





We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C



Management System ISO 9001:2015 ISO 14001:2015



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

