

Product Information

Mod.R&S 06 | Rev.4 | Update 08/2019 | Page 1



VERNICE

Description PU plotter cut heat seal material with glossy varnish effect and polyester backing. The material is very thin and grants an easy cutting, weeding and application.

> Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex (not suited for treated and sublimated textiles).

Suggested cutting settings

Average thickness

90 microns

Blade: 45° Pressure: 40 gf Speed: 30 cm/sec

- **Usage** Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - Remove the carrier cold




Transfer settings

15 seconds at 150°C (300°F) medium pressure (3-4 bar)

Wait atleast 24 hours from application before washing. **Washing** Washing resistance up to **60°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Not suitable for tumble dryer.

> The product is REACH compliant The product is VEGANOK certified





Dry cleaning



Tumble dryer







N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in

vertical position and at temperatures between 18°C and 26°C



Management System ISO 9001:2015 ISO 14001:2015



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com

For further information, please contact our Sales Office.

